

120.0 kVA JOHN DEERE GENERATOR

FEATURES & BENEFITS

- Maximum 132.0 kVA, 400 V, 1500 RPM
- Industrial brushless alternator with AVR
- Steel baseframe, retention basin & fuel tank with sensor
- 360 litre tank for 17 hrs @ 75% Load
- Test report, manuals and electrical drawings supplied
- Modular design, open and silent version available
- Industrial silencer and coupling flange
- Electrical panel mounted on board the unit with digital control device installed in metal box
- Compact for easy handling and use
- World wide after sales service and technical support





GENERAL DATA	
Model:	JD120GO
Continuous power (PRP):	120.0 kVA
Continuous power (PRP):	96.0 kW
Stand-by power (LTP):	132.0 kVA
Stand-by power (LTP):	105.6 kW
Power factor:	0.8
Frequency (Hz):	50 Hz
Voltage (V):	400 V
Width:	1140 mm
Length:	3000 mm
Height:	1770 mm
Weight:	1800 kgs
Tank Capacity:	360 l
dBa @ 7m:	N/A

ALTERNATOR	
Alternator brand:	MARELLI
Alternator model:	MJB225LA4
L.T.P. Power:	145.0 kVA
P.R.P. Power:	132.0 kVA
Connection:	Series star
Phases:	Three phases with neutral
Terminal Number:	12
IP Protection:	23
Alternate Alternator:	STAMFORD / UCI274D

ENGINE DATA	
Brand:	JOHN DEERE
Model:	6068TF258
Cylinders:	6
RPM:	1500
Cubic Capacity:	6.80
Air Intake:	Turbocharged
Standard Voltage:	12
SAE:	3-11 1/2
BMEP:	1282
Cooling:	Water
Flywheel P.R.P. Power:	105.0 kW
Flywheel Stand-by Power:	115.0 kW
Oil Qty:	19.0 l
Antifreeze Qty:	11.3 l
Heat from Radiator:	66.0 kW
Heat from Exhaust:	98.0 kW
Exhaust Temperature:	540 °C
Cooling Airflow:	150.00 m³/min
Combustion Airflow:	8.10 m³/min
Exhaust Airflow:	17.40 m³/min
TA Luft / TA Luft 2:	Standard / Not available
Stage:	Not available

FUEL CONSUMPTION	
Fuel Cons. at 110%:	30.2 l/h
Fuel Cons. at 100%:	27.1 l/h
Fuel Cons. at 75%:	20.5 l/h
Fuel Cons. at 50%:	14.2 l/h
Fuel Cons. at 25%:	7.7 l/h

* Specs subject to change without prior notice.
 * Measurements based on ISO8528-1 Standards
 * Picture may vary from actual product.