

## 60.0 kVA JOHN DEERE GENERATOR

### FEATURES & BENEFITS

- Maximum 66.0 kVA, 400 V, 1500 RPM
- Industrial brushless alternator with AVR
- Steel baseframe, retention basin & fuel tank with sensor
- 160 litre tank for 14 hrs @ 75% Load
- Test report, manuals and electrical drawings supplied
- Modular design, open and silent version available
- Industrial silencer and coupling flange
- Electrical panel mounted on board the unit with digital control device installed in metal box
- Compact for easy handling and use
- World wide after sales service and technical support





GENERAL DATA	
<b>Model:</b>	JD65GO
<b>Continuous power (PRP):</b>	60.0 kVA
<b>Continuous power (PRP):</b>	48.0 kW
<b>Stand-by power (LTP):</b>	66.0 kVA
<b>Stand-by power (LTP):</b>	52.8 kW
<b>Power factor:</b>	0.8
<b>Frequency (Hz):</b>	50 Hz
<b>Voltage (V):</b>	400 V
<b>Width:</b>	1010 mm
<b>Length:</b>	2200 mm
<b>Height:</b>	1480 mm
<b>Weight:</b>	1230 kgs
<b>Tank Capacity:</b>	160 l
<b>dBa @ 7m:</b>	N/A

ALTERNATOR	
<b>Alternator brand:</b>	MARELLI
<b>Alternator model:</b>	MJB200MA4
<b>L.T.P. Power:</b>	68.2 kVA
<b>P.R.P. Power:</b>	62.0 kVA
<b>Connection:</b>	Series star
<b>Phases:</b>	Three phases with neutral
<b>Terminal Number:</b>	12
<b>IP Protection:</b>	23
<b>Alternate Alternator:</b>	STAMFORD / UCI224E

ENGINE DATA	
<b>Brand:</b>	JOHN DEERE
<b>Model:</b>	4045TF158
<b>Cylinders:</b>	4
<b>RPM:</b>	1500
<b>Cubic Capacity:</b>	4.50
<b>Air Intake:</b>	Turbocharged
<b>Standard Voltage:</b>	12
<b>SAE:</b>	3-11 $\frac{1}{2}$
<b>BMEP:</b>	990
<b>Cooling:</b>	Water
<b>Flywheel P.R.P. Power:</b>	54.0 kW
<b>Flywheel Stand-by Power:</b>	60.0 kW
<b>Oil Qty:</b>	12.0 l
<b>Antifreeze Qty:</b>	8.5 l
<b>Heat from Radiator:</b>	0.0 kW
<b>Heat from Exhaust:</b>	0.0 kW
<b>Exhaust Temperature:</b>	492 °C
<b>Cooling Airflow:</b>	0.00 m <sup>3</sup> /min
<b>Combustion Airflow:</b>	4.40 m <sup>3</sup> /min
<b>Exhaust Airflow:</b>	9.50 m <sup>3</sup> /min
<b>TA Luft / TA Luft 2:</b>	Standard / Not available
<b>Stage:</b>	Not available

FUEL CONSUMPTION	
<b>Fuel Cons. at 110%:</b>	15.6 l/h
<b>Fuel Cons. at 100%:</b>	14.1 l/h
<b>Fuel Cons. at 75%:</b>	10.8 l/h
<b>Fuel Cons. at 50%:</b>	7.5 l/h
<b>Fuel Cons. at 25%:</b>	4.6 l/h

\* Specs subject to change without prior notice.  
 \* Measurements based on ISO8528-1 Standards  
 \* Picture may vary from actual product.