

## 80.0 kVA JOHN DEERE GENERATOR

### FEATURES & BENEFITS

- Maximum 88.0 kVA, 400 V, 1500 RPM
- Industrial brushless alternator with AVR
- Steel baseframe, retention basin & fuel tank with sensor
- 160 litre tank for 11 hrs @ 75% Load
- Test report, manuals and electrical drawings supplied
- Modular design, open and silent version available
- Industrial silencer and coupling flange
- Electrical panel mounted on board the unit with digital control device installed in metal box
- Compact for easy handling and use
- World wide after sales service and technical support



ABB

VISA

GENERAL DATA	
<b>Model:</b>	JD80GO
<b>Continuous power (PRP):</b>	80.0 kVA
<b>Continuous power (PRP):</b>	64.0 kW
<b>Stand-by power (LTP):</b>	88.0 kVA
<b>Stand-by power (LTP):</b>	70.4 kW
<b>Power factor:</b>	0.8
<b>Frequency (Hz):</b>	50 Hz
<b>Voltage (V):</b>	400 V
<b>Width:</b>	1010 mm
<b>Length:</b>	2500 mm
<b>Height:</b>	1480 mm
<b>Weight:</b>	1230 kgs
<b>Tank Capacity:</b>	160 l
<b>dBa @ 7m:</b>	N/A

ALTERNATOR	
<b>Alternator brand:</b>	MARELLI
<b>Alternator model:</b>	MJB225SA4
<b>L.T.P. Power:</b>	94.0 kVA
<b>P.R.P. Power:</b>	85.0 kVA
<b>Connection:</b>	Series star
<b>Phases:</b>	Three phases with neutral
<b>Terminal Number:</b>	12
<b>IP Protection:</b>	23
<b>Alternate Alternator:</b>	STAMFORD / UCI224G

ENGINE DATA	
<b>Brand:</b>	JOHN DEERE
<b>Model:</b>	4045TF258
<b>Cylinders:</b>	4
<b>RPM:</b>	1500
<b>Cubic Capacity:</b>	4.50
<b>Air Intake:</b>	Turbocharged
<b>Standard Voltage:</b>	12
<b>SAE:</b>	3-11 1/2
<b>BMEP:</b>	1333
<b>Cooling:</b>	Water
<b>Flywheel P.R.P. Power:</b>	72.0 kW
<b>Flywheel Stand-by Power:</b>	80.0 kW
<b>Oil Qty:</b>	12.0 l
<b>Antifreeze Qty:</b>	8.5 l
<b>Heat from Radiator:</b>	45.0 kW
<b>Heat from Exhaust:</b>	67.0 kW
<b>Exhaust Temperature:</b>	565 °C
<b>Cooling Airflow:</b>	0.00 m³/min
<b>Combustion Airflow:</b>	5.60 m³/min
<b>Exhaust Airflow:</b>	12.30 m³/min
<b>TA Luft / TA Luft 2:</b>	Standard / Not available
<b>Stage:</b>	Not available

FUEL CONSUMPTION	
<b>Fuel Cons. at 110%:</b>	21.5 l/h
<b>Fuel Cons. at 100%:</b>	19.5 l/h
<b>Fuel Cons. at 75%:</b>	14.0 l/h
<b>Fuel Cons. at 50%:</b>	10.0 l/h
<b>Fuel Cons. at 25%:</b>	5.0 l/h

\* Specs subject to change without prior notice.

\* Measurements based on ISO8528-1 Standards

\* Picture may vary from actual product.