

VOLVO-PENTA

V415GO

GENERAL DATA

Model	V415GO
Continuous / Prime power (P.R.P)	410,00 kVA
Continuous / Prime power (P.R.P)	328,00 kW
Stand-by power (L.T.P)	450,00 kVA
Stand-by power (L.T.P)	360,00 kW
Power Factor / Cos (ϕ)	0.8
Frequency	50 Hz
Voltage	400/230 V
No. phases	Three Phases
Engine Speed	1500 rpm

DIMENSIONS*

Length (-L- m)	4000 mm
Width (-W- m)	1300 mm
Height (-H- m)	2414 mm
Weight (kg)	4900 kg
Tank Capacity	400 l

ENGINE

Brand	VOLVO-PENTA
Model	TAD1344GE
No. of Cylinders	6
Cubic capacity	12,78 l
Air intake	Turbocharged
Cooling	Water
Flywheel net power	354 kW
BMEP	
SAE:	

ENGINE TECHNICAL DATA

Oil Qty	
Antifreeze Qty	
Cooling air flow	
Combust. air flow	
Exhaust gas flow	

FUEL CONSUMPTION @ LOAD

100% (Standby)	90,3 l/h
100% (Prime)	81,8 l/h
75%	62,3 l/h
50%	42,1 l/h
25%	23,1 l/h



ALTERNATOR

Brand	MARELLI
Model	MJB315MA4
Continuous power	410,00 kVA
Stand-by power	450,00 kVA
Connection	Stella Series

STARTING BATTERY

Capacity	120 Ah
Quantity	2
Voltage	24 V

FLEXIBLE PIPE

Model	DN125
Quantity	1
Diameter	140 mm

EXHAUST SILENCER

Model	MSR/a 125
Quantity	1
Diameter	140 mm

* Figures are subject to change without prior notice.

** The mentioned power values are according to ISO8528-1 Standards