

750.0 kVA PERKINS GENERATOR

FEATURES & BENEFITS

- Maximum 825.0 kVA, 400 V, 1500 RPM
- Industrial brushless alternator with AVR
- Steel baseframe, retention basin & fuel tank with sensor
- Connect directly to a bulk tank (No integrated tank)
- Test report, manuals and electrical drawings supplied
- Modular design, open and silent version available
- Industrial silencer and coupling flange
- Electrical panel mounted on board the unit with digital control device installed in metal box
- Compact for easy handling and use
- World wide after sales service and technical support



GENERAL DATA	
Model:	P730S
Continuous power (PRP):	750.0 kVA
Continuous power (PRP):	600.0 kW
Stand-by power (LTP):	825.0 kVA
Stand-by power (LTP):	660.0 kW
Power factor:	0.8
Frequency (Hz):	50 Hz
Voltage (V):	400 V
Width:	2200 mm
Length:	5700 mm
Height:	2950 mm
Weight:	9200 kgs
Tank Capacity:	0 l
dBa @ 7m:	72.0 dBA

ALTERNATOR	
Alternator brand:	MARELLI
Alternator model:	MJB355MB4
L.T.P. Power:	880.0 kVA
P.R.P. Power:	800.0 kVA
Connection:	Star
Phases:	Three phases with neutral
Terminal Number:	6
IP Protection:	23
Alternate Alternator:	STAMFORD / HCI6G

ENGINE DATA	
Brand:	PERKINS
Model:	4006-23TAG2A
Cylinders:	6
RPM:	1500
Cubic Capacity:	22.92
Air Intake:	Turbocharged
Standard Voltage:	24
SAE:	0-18
BMEP:	2295
Cooling:	Water
Flywheel P.R.P. Power:	632.0 kW
Flywheel Stand-by Power:	695.0 kW
Oil Qty:	122.7 l
Antifreeze Qty:	51.0 l
Heat from Radiator:	231.0 kW
Heat from Exhaust:	500.0 kW
Exhaust Temperature:	430 °C
Cooling Airflow:	1200.00 m ³ /min
Combustion Airflow:	64.00 m ³ /min
Exhaust Airflow:	180.00 m ³ /min
TA Luft / TA Luft 2:	On request / On request
Stage:	Not available

FUEL CONSUMPTION	
Fuel Cons. at 110%:	176.0 l/h
Fuel Cons. at 100%:	161.0 l/h
Fuel Cons. at 75%:	122.0 l/h
Fuel Cons. at 50%:	83.0 l/h
Fuel Cons. at 25%:	0.0 l/h

* Specs subject to change without prior notice.
 * Measurements based on ISO8528-1 Standards
 * Picture may vary from actual product.