

10 KVA LPG / NATURAL GAS GENERATOR

FEATURES & BENEFITS

- Maximum 11 kVA, 230V, 3000RPM
- Generac's OHVI® engine is purpose-built for the rigors of generator use.
- Sturdy, enclosure with RhinoCoat™ finish for superior weather protection
- External "at-a-glance" indicator lights
- Tool-Less fuel conversion (LPG / NG)
- 3 yr. / 1000 hr. Limited Warranty
- Unique Canopy design for easy access
- Completely Weatherproof
- Environmentally Friendly
- Better fuel consumption than diesel



GENERAL DATA

Model:	BP10S-G
Prime Power (P.R.P):	10 kVA
Stand-by Power (L.T.P):	11 kVA
Amps:	45 A
Power Factor / COS:	1
Frequency:	50 Hz
Voltage:	230 V
Phases:	Single Phase
Engine Speed:	3000 RPM
Length:	1218 mm
Width:	638 mm
Height:	732 mm
Weight:	197 kg's
Tank Capacity:	N/A l

ADDITIONAL

Running Time (p/tank):	
Structure Type:	Silent Steel Enclosure
Noise Level (7m):	62 - 66 dBA
Auto Voltage Regulator:	Constant voltage AVR
ISO9001 Certified:	Yes
CE Certified:	Yes
Fuel Cons. @ 100% Load:	7.3

ENGINE DATA

Brand:	Generac
Model:	OVHI V-TWIN
Type:	2 Cylinder V-Twin OVHI, Air Cooled
Starting System:	12 Volt Electric Starter
Auto-Decompression:	Yes
Cubic Capacity (l):	0.992
Compression Ratio:	9.5:1
Rated Power (kW/RPM):	10 kW
Fuel Type:	LPG / NATURAL GAS
Lube Oil:	Multigrade / 20W50
Low Pressure Alert:	Yes
Low Fuel Cut Out:	Yes

CONTROL PANEL

Model:	Evolution
Type:	Digital Control Panel
Analogue Inputs:	N/A
Mains Phase Voltage:	Yes
Mains Line Voltage:	Yes

ALTERNATOR

Model:	-
Pole Number:	2
Excitation Mode:	Self Excitation and Constant Voltage (AVR)

* Specs subject to change without prior notice. E&OE.

* Measurements based on ISO8528-1 Standards

* All rating at Sea Level. 25°C Ambient Temp.