

1.8 KVA PETROL GENERATOR

FEATURES & BENEFITS

- Maximum 2.0 kVA, 230V, 4300 Smart ThrottledRPM
- Recoil Starter
- Low noise design
- 3.6 Litre Fuel Tank, 5 Hours @ 75% load
- DC output 12 volts, Battery Charging Facility
- Powerful Four Stroke Petrol Engine
- Overload Alarm LED and Shutdown for Engine Protection
- Voltage Output Indicator LED
- Hour Meter tracks usage for proper service intervals
- 230 volt plug sockets x 2



GENERAL DATA	
Model:	BP2S
Prime Power (P.R.P):	1.8 kVA
Stand-by Power (L.T.P):	2.0 kVA
Amps:	7.5 A
Power Factor / COS:	1
Frequency:	50 Hz
Voltage:	230 V
Phases:	Single Phase
Engine Speed:	4300 Smart Throttled RPM
Length:	555 mm
Width:	305 mm
Height:	460 mm
Weight:	24 kg's
Tank Capacity:	3.6 l

ADDITIONAL	
Running Time (p/tank):	5 Hours @ 75% load
Structure Type:	Silent / Suitcase Style
Noise Level (7m):	59-64db @ 7m dBA
Auto Voltage Regulator:	N/A
ISO9001 Certified:	Yes
CE Certified:	Yes
Fuel Cons. @ 100% Load:	0.9
Fuel Cons. @ 75% Load:	0.7
Fuel Cons. @ 50% Load:	0.5

ENGINE DATA	
Brand:	Bundu Power
Model:	160F
Type:	4 stroke, overhead air valve, one cylinder
Starting System:	Recoil Pull Start
Auto-Decompression:	Yes
Cubic Capacity (l):	0.113
Compression Ratio:	8.8:1
Rated Power (kW/RPM):	2 KW
Fuel Type:	Petrol
Lube Oil:	10W-30 / SAE30
Low Pressure Alert:	Yes
Low Fuel Cut Out:	Yes

CONTROL PANEL	
Model:	N/A
Type:	Hour Meter
Analogue Inputs:	N/A
Mains Phase Voltage:	N/A
Mains Line Voltage:	N/A

ALTERNATOR	
Model:	N/A
Pole Number:	N/A
Excitation Mode:	N/A

* Specs subject to change without prior notice. E&OE.

* Measurements based on ISO8528-1 Standards

* All rating at Sea Level, 25°C Ambient Temp.