

5.0 KVA PETROL GENERATOR

FEATURES & BENEFITS

- Maximum 7.0 kVA, 230V, 3000RPM
- The Generac OHV engine, splash lubricated
- Large-capacity steel fuel tank with fuel gauge
- 27 Litre Fuel Tank, 6 Hours @ 75% load
- Circuit breaker protected outlets
- High leverage fold-down handle
- Never-flat wheels for reliable portability
- Hardened 1 1/4" steel tube cradle for added strength and durability
- Hour Meter tracks usage for proper service intervals
- High Quality American Built



GENERAL DATA

Model:	BP5000-G
Prime Power (P.R.P):	5.0 kVA
Stand-by Power (L.T.P):	7.0 kVA
Amps:	21.7 A
Power Factor / COS:	1
Frequency:	50 Hz
Voltage:	230 V
Phases:	Single Phase
Engine Speed:	3000 RPM
Length:	692 mm
Width:	687 mm
Height:	638 mm
Weight:	81 kg's
Tank Capacity:	27 l

ADDITIONAL

Running Time (p/tank):	6 Hours @ 75% load
Structure Type:	Open Frame
Noise Level (7m):	N/A dBA
Auto Voltage Regulator:	Yes
ISO9001 Certified:	Yes
CE Certified:	Yes
Fuel Cons. @ 100% Load:	5.5
Fuel Cons. @ 75% Load:	4.2
Fuel Cons. @ 50% Load:	2.8

ENGINE DATA

Brand:	Generac
Model:	OVH
Type:	OVH Petrol, Air Cooled
Starting System:	Recoil Pull Start
Auto-Decompression:	Yes
Cubic Capacity (l):	0.389
Compression Ratio:	8.5:1
Rated Power (kW/RPM):	5 KW
Fuel Type:	Petrol
Lube Oil:	10W-30 / SAE30
Low Pressure Alert:	Yes
Low Fuel Cut Out:	Yes

CONTROL PANEL

Model:	N/A
Type:	Hour Meter
Analogue Inputs:	N/A
Mains Phase Voltage:	N/A
Mains Line Voltage:	N/A

ALTERNATOR

Model:	-
Pole Number:	2
Excitation Mode:	

* Specs subject to change without prior notice. E&OE.

* Measurements based on ISO8528-1 Standards

* All rating at Sea Level, 25°C Ambient Temp.